## 10.3 x 38.1MM CARTRIDGE FUSE BLOCKS

EAT•N Bussmann

Part Number Description BM6031PO Single Pole Block. DRA-I Din Rail Adapter (35mm). SAMI-7N Non-indicating Cover.

Rating: 30A (Screw Terminal), 20A (Quick Connect Terminal).

Voltage: 600VAC / 1000VDC

Suit Fuse UL: 10.3 x 38.1mm, Midget Fuses (100mA to 30A) **Suit Fuse IEC:** 10.3 x 38.1 mm, CH10 (gG, aM) 1038 (aR, gR) etc **Suit Fuse PV:** 10.3 x 38.1 mm, PV Fuses (gPV) 600VDC to 1000VDC

Wire Size: #10-#14 (CU only)

Pack Size (box): 10, 100 Material: Thermoplastic (Base & Cover)

Flammability: UL94VO (Base), UL94-V2 (Cover)

Terminals: Tin plated, copper alloy. Screw terminal & 2 x Q.C. terminals.

Options: Base also available in 2 or 3 poles.

Mounting: Single screw fixing or DIN rail (35mm) when used with optional adapter (DRA-1). Covers: Snap on to individual fuses installed in fuse blocks, covering exposed live clips and terminals and reducing accidental contact by personnel. Suit both Class CC or Midget fuses.


Notes: Fuse not included. Approvals: ( SN (E




Fuse Cover

I/4" Ouick Connect & Screw terminals included on each end of the block. **Fuse Block** 







### 4 x 51MM FUSE BLOCKS



Part Number Description 70506U Single Pole Block

Rating: 50A

Voltage: 750VAC I.R.: 200kA @ 750VAC Mounting: Mounting Screws #10 (0.19" Dia)

Connector Type: Box lug

Maximum Wire Size: #2-14, A1/Cu Suit Fuse Dimensions: 14 x 5 lmm

Suit Fuse Types;

IEC: CH14 (gG, aM) 1451 (aR, gR) 50A max. UL: Class K5, RK1, RK5 (125mA-30A) Notes: Extra poles also available.

Approvals: (8 5)

# Swe-Check 🗫

## 22 x 58MM FUSE BLOCKS



#### Features:

• Slide lock gangable to create multiple poles.

• DIN Rail or Screw Mounting.

• Optional IP20 indicating / non indicating covers.

Part Number Description IM70100-1CR Single Pole Block CVR-J-60060 Non-indicating Cover

Rating: 100A

Voltage: 700VAC/DC I.R.: 200kA @ 700VAC Connectors: Screw terminals, tin plated alum. Maximum Wire Size: #2 to #3 AWG

Suit Fuse Dimensions: 20 x 57mm or 22 x 58mm

Suit Fuse Types; IEC: CH22 (gG, aM) 2258 (aR, gR) 100A max.

UL: Class | (IA to 30A) Approvals: @ 🖘

Email: sales@swe-check.com.au Phone: (+61) 03 9521 6133