MAXI FUSE 6 WAY SEALED FUSE HOLDER



This MAXI fuse holder is designed to fit 6 fuses in a compact, durable and a sealed solution for the transportation market. Modules can be interlocked together or interlocked with other GEP PDM-R series modules.



Voltage Rating: 32VDC

Terminal Rating: Varies by terminal and connected cable.

Temperature Rating: -40°C to + 125°C.

Housing: Black thermoplastic. Seal: Silicone, blue.

Mounting: Top mount with insert. Side mount also available. Cable Seals: Please check the overall diameter of your cable before ordering cable seals. Silicone material UL94-V0.

Cavity Plugs: Required to fill unused output cavities for ingress

protection. Silicone material.

Ingress Protection Rating: IP66.

Components: Fuses, TPA's, terminals, cable seals and cavity plugs are not included and can be ordered separately.

Approvals: RoHS

Part Number Description

PDM-R3DCI PDM 6 x Fuse Housing, Cover & Seal

PDM-TT4 TPA Terminal Position Assurance, 6pcs Required


PDM-TCT PDM Tether Black





TERMINALS: Lear Mak8 Plus

Female sealed - Copper



#7 - #5 28243306710 10.0 - 16.0 Silver

CABLE SEALS:

Silicone, GEP



Part Number	Cable Dia. (mm)	Colour
PDM-TWS-SI	2.7 - 3.0	Green
PDM-TWS-S2	3.4 - 3.8	Purple
PDM-TWS-S3	4.0 - 4.5	Orange
PDM-TWS-S4	4.6 - 5.3	Light Blue
PDM-TWS-S5	5.8 - 6.6	Gray

CAVITY PLUG:

Silicone, GEP



Part Number PDM-TWS-P





RELATED PRODUCTS:




Maxi Fuses

Datasheet: 9047


Email: info@prolecproducts.com Web: www.prolecproducts.com








Terminal Numbering (Rear of Unit)













Dimensions in MM



Ganged Units



Units are Gangable

*Dimension increases by 56.5mm for each additional module



Email: info@prolecproducts.com Web: www.prolecproducts.com Page: 2