

LOW PROFILE MINI FUSE 58V



SILVER PLATED


The low profile Mini fuse features a lower overall height thereby reducing space requirements whilst still retaining similar performance characteristics to the standard Mini fuse.



Part Number	Ampere Rating	Body Colour
LPM002	2A	Grey
LPM003	3A	Violet
LPM004	4A	Pink
LPM005	5A	Tan
LPM07.5	7.5A	Brown
LPM010	10A	Red
LPM015	15A	Blue
LPM020	20A	Yellow
LPM025	25A	Natural
LPM030	30A	Green
LPM000AP	Assortment Pack 5pcs	7.5A, 10A, 15A, 20, 30A



Assortment Pack



Voltage: 58VDC **I.R.:** 1000A at 58VDC

Characteristic: Fast Acting

Pack Size: 5, 10, 100, 1000

Terminals: Zinc alloy, silver plated.

Holders: PCB Clips and bases please contact sales.

Approvals: SAE RoHS

RELATED PRODUCTS:



Fuse Puller
(see p.44)



Fuse Holder
(see p.72)



Fuse Kit
(see p.38)



Add-a-circuit
(see p.83)

MINI TYPE DEVICES

Diode / Resistor
Shunt / Transorb



Diode, Resistor, Shunt and Transorb vehicle-style electrical protection devices easily install in common Mini fuse holders and provide voltage and current limiting functionality to vehicle circuitry.



Part Number	Description	Profile	Brand
02400113P	Diode - 1A, (400V PIV). Keyed*. Reverse current protector.	Standard	Littelfuse
22903-6	Diode - 6A. Keyed*. Reverse current protector.	Tall	Bussmann
22903-6V	Diode - 6A. Keyed & Wing*. Reverse current protector.	Tall	Bussmann
22902-68	Resistor - 5W. Resistance: 68Ω. Voltage drop device.	Tall	Bussmann
0297900*	Shunt - 20A Maximum continuous load rating.	Standard	Littelfuse NEW
22901-1.5	Transorb - Clamp Rating: 27VDC. Power Rating: 1500W. Voltage spike protector.	Tall	Littelfuse

Materials: Thermoplastic housing, grey with metal cover (229 series).
Thermoplastic housing, black (02400113P).

Termination Type: 2.8mm blades. Compatible with ISO 280 type fuse blocks.

Diode Key Feature*: Standard key denotes installation direction.

Wing key available for error proof installation in Bussmann VEC.

Holders: Please refer to our holder compatibility table on our QR datasheet.

Pack Size: Stock lines 1pc. *Indent items contact sales

Scan this QR Code for more information



QR Code: 3001



Diode
02400113P



Diode
22903-6



Diode
22903-6V



Resistor
22902-68



Shunt
0297900



Transorb
22901-1.5