## **ANL LIFT TRUCK FUSES 80V**

Forklift truck and battery isolator fuses are specially designed for the heavy duty loads associated with DC battery powered equipment such as forklift trucks, hand trucks, motorized work platforms, and other DC battery operated systems. Rugged construction and stud mounted bolt-in design assure a long life in adverse conditions.

Part Number ANL035 ANL040 ANL050 ANL050 ANL060 ANL00 ANL100 ANL125 ANL130 ANL150 ANL175	Ampere Rating 35A 40A 50A 60A 80A 100A 125A 130A 150A 175A	Part Number ANL225 ANL250 ANL275 ANL300 ANL325 ANL350 ANL400 ANL600 ANL605	Ampere Rating 225A 250A 275A 300A 325A 350A 400A 500A 600A 675A
ANL175 ANL200			
ANL200	200A	ANL750	750A

I.R.: 6kA (35A to 500A, 32VAC), 2.7kA (600A to 750A, 32VAC) 2.7kA (All ratings, 80VDC) Voltage: 32VAC / 80VDC Characteristic: Fast Acting **Features:** Ignition Proof (<500A). Silver plated copper link. Mounting: M8 or 5/16" studs Features: Element visible inspection mica window. Holders: Block. Pack Size: 1, 5, 10, 100 Approvals: SAE Ignition Protected (35A to 500A) 🔊 (600A, 675A & 750À ratings) RoHS

RELATED **PRODUCTS:** 



## **ANN LIFT TRUCK FUSES 80V**


Part	Amper	e	Part	Ampere
Number	Rating		Number	Rating
ANN010	I0A		ANN225	225A
ANN035	35A		ANN250	250A
ANN040	40A		ANN275	275A
ANN050	50A		ANN300	300A
ANN060	60A		ANN325	325A
ANN080	80A		ANN350	350A
ANN090	90A		ANN400	400A
ANN I 00	100A		ANN500	500A
ANN125	125A		ANN600	600A
ANN I 50	150A		ANN700	700A
ANN175	175A		ANN800	800A
ANN200	200A			

I.R.: 2.5kA (125VAC), 2.7kA (80VDC) Voltage: 125VAC / 80VDC Characteristic: Very Fast Acting Mounting: M8 or 5/16" studs Features: Element visible inspection mica window. Holders: Block. Pack Size: 1, 5, 10, 100 Notes: ANN series is not ignition proof Approvals: 9 (35A-400A, 500A DC only)

RELATED **PRODUCTS:** 







**E1**•**N** Bussmann


SILVER IGNITION IGNITION



ANL Series	Dimensions in MM		
Ampere Rating	A	B	
35Å to 200A	0.45	7.55	
225A to 325A	1.40	8.70	
350A to 675A	2.70	9.50	
750A	3.35	10.9	

## E T • N Bussmann





ANN Series	Dimensions in MM		
Ampere Rating	A	B	
10A to 300A	1.19	9.12	
325A to 600A	4.47	12.70	
700A to 800A	5.94	13.49	

