## **3AG 250V IN-LINE HOLDER SPLASH PROOF**

Part Number HFA-R

Rating: 20A Voltage: 250V Flammability: UL 94 HB (phenolic body) Temperature Rating (RTI): 150°C Holder Type: Bayonet Type Ingress Protection: IP64 Rating for exposed locations. Contacts: Copper crimp **Crimp Terminal:** I - 3mm<sup>2</sup>(#16-12AWG) copper wire. Crimp Tool: Thomas & Betts WT-112M Pack Size: 1, 10, 20, 100, 500 Approvals: 🔊 RoHS

### **RELATED PRODUCTS:**



AGC / 3AG Fuses (see p. 10 & 11)

**3AB** Fuses (see p.11)

## **3AG 32V IN-LINE HOLDER & 20A FUSE**



HRI

Part Number Description 20A Bayonet holder

Voltage: 32V Temperature Rating (RTI): 140°C. Wire Thickness: 2mm<sup>2</sup> (#14 AWG). Wire Length: 480mm loop. Pack Size: 1, 10, 100, 500, 1000


#### **Bonus Feature:**

Fuse holder includes 3AG 20A fuse. # AGC020 Fuse specifications: Glass case 6.35 x 31.8mm 20A 32VAC/DC





**E T** • **N** Bussmann



# **3AG 32V IN-LINE HOLDER**

Part Number Description HHN 30A Twist lock holder

#### Voltage: 32V

Body: Nylon Heavy Duty White Body. Wire Thickness: 3mm<sup>2</sup> (#12 AWG) yellow. Wire Length: 2 x 100mm lengths of wire. Pack Size: 1, 10, 100, 500, 1000 Notes: Fuse is not included

### **RELATED PRODUCTS:**








**AGC** Fuse Kit (see p.38)





E-T-N

Dimensions in MM



Email: info@prolecproducts.com.au Web: www.prolecproducts.com.au



NEW

Bussmann

Bussmann



E AT • N

**Crimp Terminal** 

