MINI FUSE IN-LINE HOLDERS



IGNITION

Part Number Description

FHM001 20A with cover, 2.1mm² #14AWG Black FHM002 30A with cover, 3.3mm² #12AWG Orange

Voltage: 32V-58V

Wire: 125°C rated, GXL wires, tinned stranded copper.

Body: Black thermoplastic Ignition Proof: UL94 Ignition Protection: V-2 / V-0

Ingress Rating: IP67 Cover dustproof & waterproof.


Pack Size: 1, 10, 100, 1000 Note: Fuses are not included.

Approvals: RoHS





Mini Fuse 58V **RFI ATFD** Mini Fuse PRODUCTS: (see p.15) (see p. 16)



MINI FUSE IN-LINE HOLDER

Part Number Description

HHL 20A with cover. I.0mm² # I6AWG

Voltage: 32V

Wire: Black, 26 strand copper, no plating. Contact Material: Brass, tin-plated. Insulation Body: Santoprene TPV. Feature: Cover is splash proof Pack Size: 1, 10, 100, 1000


Approvals: (1) 3266, SAE | 2030 RoHS

RELATED PRODUCT: Mini Fuse (see p.15)



Bussmann IP66

FATON



MINI FUSE IN-LINE HOLDERS CLEAR



FHM00XCLR is a transparent inline fuse holder with protective cap that when used with a LED indicating mini blade fuse it lights up when a fuse is blown.

Part Number

FHM002CLR 30A with clear cover, 3.3mm² # I2AWG


Description FHM001CLR 20A with clear cover, I.0mm² # I6AWG

Voltage: 32V Wire Length: 2 x 125mm lengths of wire **Body:** Transparent thermoplastic Feature: Cover is splash proof Pack Size: 1, 10, 100, 1000

Approvals: RoHS

LED Mini Fuse RELATED PRODUCT: (see p.15)





Blown LED Mini Fuse Lights Up Clear Cover



Email: info@prolecproducts.com.au Web: www.prolecproducts.com.au