

Part Number	Ampere Rating	AC Voltage	DC Voltage	Total I ² t at Rated VAC
FWC-1A10F	1A	700V	700V	1.2
FWC-2A10F	2A	700V	700V	3.0
FWC-3A10F	3A	700V	700V	11
FWC-4A10F	4A	700V	700V	32
FWC-6A10F	6A	600V	700V	30
FWC-8A10F	8A	600V	700V	50
FWC-10A10F	10A	600V	700V	70
FWC-12A10F	12A	600V	700V	120
FWC-16A10F	16A	600V	700V	150
FWC-20A10F	20A	600V	700V	260
FWC-25A10F	25A	600V	700V	390
FWC-32A10F	32A	600V	-	600

FWX-1A14F	1A	250V	250V	0.4
FWX-2A14F	2A	250V	250V	0.1
FWX-3A14F	3A	250V	250V	0.26
FWX-4A14F	4A	250V	250V	0.23
FWX-5A14F	5A	250V	250V	13
FWX-10A14F	10A	250V	250V	24
FWX-15A14F	15A	250V	250V	83
FWX-20A14F	20A	250V	250V	200
FWX-25A14F	25A	250V	250V	300
FWX-30A14F	30A	250V	250V	500

FWP-1A14F	1A	700V	700V	0.41
FWP-2A14F	2A	700V	700V	0.11
FWP-2.5A14F	2.5A	700V	700V	TBC
FWP-3A14F	3A	700V	700V	0.26
FWP-4A14F	4A	700V	700V	0.23
FWP-5A14F	5A	700V	800V	11
*FWP-10A14F	10A	700V	800V	38.5
*FWP-15A14F	15A	700V	800V	70
*FWP-20A14F	20A	700V	800V	230
*FWP-25A14F	25A	700V	800V	375
*FWP-30A14F	30A	700V	800V	485
*FWP-32A14F	32A	700V	800V	600
*FWP-40A14F	40A	700V	800V	750
*FWP-50A14F	50A	700V	800V	1800

*FWP-20A22F	20A	700V	500V	260
*FWP-25A22F	25A	700V	500V	410
*FWP-32A22F	32A	700V	500V	605
*FWP-40A22F	40A	700V	500V	750
*FWP-50A22F	50A	700V	500V	1600
*FWP-63A22F	63A	700V	500V	3080
*FWP-80A22F	80A	700V	500V	6600
*FWP-100A22F	100A	700V (UL) 600V (IEC)	500V	12500

Series:	I.R.:
FWC...10F	200kA RMS Sym. @ 600VAC (6-32A)
FWC...10F	200kA at 700VAC (1A to 4A)
FWC...10F	50kA at 600VDC (6A to 25A)
FWC...10F	50kA at 700VDC (1A to 4A)
FWX...14F	200kA at 250VAC
FWX...14F	50kA at 250VDC
FWP...14F	200kA at 690VAC (IEC)
FWP...14F	200kA at 700VAC (UL)
FWP...14F	50kA at 800VDC (5A to 50A)
FWP...22F	200kA at 690VAC (IEC)
FWP...22F	200kA at 700VAC (UL)
FWP...22F	50kA at 500VDC

FWC...10F




Dimensions in mm

FWX...14F



FWP...14F



Optional Striker Indicator

FWP...22F



Optional Striker Indicator

Voltage: refer to I.R. table for details.

Pack Size: 10pcs

Holders: Clips, Blocks, Carriers, Inline & Panel Mount, see fuse holder section or contact sales.

Features: * Striker indicators also available.

To order this version add "i" the part number suffix.

Note: Striker version is 600Vdc only.

Approvals Available: IEC